



Предназначение / Purpose	Р	В	К	С	П	Н			
	○	●	○	○	□	□	151581РП(Н)70	151581РП(Н)90	
	○	●	○	○	□	□	151581ВП(Н)70	151581ВП(Н)90	
	○	●	○	○	□	□	151581КП(Н)70	151581КП(Н)90	
	○	●	○	○	□	□	151581СП(Н)70	151581СП(Н)90	
	□	□			□	□			152112
	□	□			□	□			152114
	□	□			□	□			152116
	□	□			□	□			152118
Междучентрие / Distance	(mm)		70		90				

ПРИЛОЖЕНИЕ

Дръжките са с ергономичен дизайн и са предназначени за леви и десни врати на входни, вътрешни и сервизни помещения, както и за прозорци.

ХАРАКТЕРИСТИКИ

- * Шилдове от стомана. Покритие: никел или полимер
- * Дръжки от Zn-Al-Cu сплав. Покритие: никел или полимер
- * Гайка от стомана. Покритие: цинк
- * Винтове от стомана. Покритие: цинк.
- * Квадрат от стомана 8x8 мм. Покритие: цинк.

ПО ПОРЪЧКА

Дръжки с междуцентрие 72мм и 85мм

APPLICATION

Handles are ergonomically designed and are used in left and right doors for entrance, interior, bathroom and windows.

FEATURES

- * Shield is made of steel, nickel or polymer finished.
- * Handle is made of Zn Al Cu alloy, nickel or polymer finished.
- * The nut is made of steel, zinc finished.
- * Steel screws. Brass plated.
- * Steel square 8x8 mm. Zinc plated.

CUSTOMERS ORDER

- * We can offer handles with distance between axis 72 mm. and 85 mm.

